| FARAI  | General data 6-pins EF16/8/5<br>PARAMETER   |   | SPECIFICATION   |   |  |  |
|--|---|---|---|---|--|--|
| PAKAMETEK  |   |   |   |   |  |  |
| Coil former material   |   | Polyethylene terephtalate (PET), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E41938 |   |   |  |  |
| Pin material   |   | copper-tin alloy (CuSn), tin (Sn) plated  |   |   |  |  |
| Maximum operating temperature  |   | 155 °C, "IEC 60085", class F  |   |   |  |  |
| Resistance to soldering heat   |   | "IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s   |   |   |  |  |
| Soldeerability   |   | "IEC 60068-2-20", Part 2, Test Ta, method 1   |   |   |  |  |
|  |   |   |   |   |  |  |
|  |   |   |   |   |  |  |
| Winding data a   | and area product                            | -   | 1   |   |  |  |
|  | WINDING                                     | MINIMUM   | AVERAGE   | AREA  |  |  |
| NUMBER OF  | WINDING                                     | -   | 1   |   | TYPE NUMBER  |  |
|  | WINDING                                     | MINIMUM   | AVERAGE<br>LENGTH OF  | AREA<br>PRODUCT   | TYPE NUMBER  |  |
| NUMBER OF  | WINDING                                     | MINIMUM<br>WINDING<br>WIDTH   | AVERAGE<br>LENGTH OF<br>TURN  | AREA<br>PRODUCT<br>Ae x Aw  | TYPE NUMBER  |  |
| NUMBER OF<br>SECTIONS  | WINDING                                     | MINIMUM<br>WINDING<br>WIDTH<br>(mm)<br>3*2.80   | AVERAGE<br>LENGTH OF<br>TURN<br>(mm)<br>37  | AREA<br>PRODUCT<br>Ae x Aw<br>(mm <sup>4</sup> )<br>610                               | TYPE NUMBER<br>EF-1602-2-3S-6P   |  |
| NUMBER OF<br>SECTIONS  | WINDING<br>AREA<br>(mm <sup>2</sup> )<br>32 | MINIMUM<br>WINDING<br>WIDTH<br>(mm)<br>3*2.80   | AVERAGE<br>LENGTH OF<br>TURN<br>(mm)<br>37  | AREA<br>PRODUCT<br>Ae x Aw<br>(mm <sup>4</sup> )<br>610                               | EF-1602-2-3S-6P  |  |
| NUMBER OF<br>SECTIONS<br>1<br>folerances unless of<br>>L≤4±0.10 4 <l≤<br>6<l≤45±0.30 45<="" td=""><td>WINDING<br/>AREA<br/>(mm<sup>2</sup>)<br/>32</td><td>MINIMUM<br/>WINDING<br/>WIDTH<br/>(mm)<br/>3*2.80</td><td>AVERAGE<br/>LENGTH OF<br/>TURN<br/>(mm)<br/>37</td><td>AREA<br/>PRODUCT<br/>Ae x Aw<br/>(mm<sup>4</sup>)<br/>610<br/>RE</td><td>EF-1602-2-3S-6P</td></l≤45±0.30></l≤<br>  | WINDING<br>AREA<br>(mm <sup>2</sup> )<br>32 | MINIMUM<br>WINDING<br>WIDTH<br>(mm)<br>3*2.80   | AVERAGE<br>LENGTH OF<br>TURN<br>(mm)<br>37  | AREA<br>PRODUCT<br>Ae x Aw<br>(mm <sup>4</sup> )<br>610<br>RE                         | EF-1602-2-3S-6P  |  |
| NUMBER OF<br>SECTIONS<br>1<br>folerances unless of<br>>L≤4±0.10 4 <l≤<br>6<l≤45±0.30 45<="" td=""><td>WINDING<br/>AREA<br/>(mm<sup>2</sup>)<br/>32</td><td>MINIMUM<br/>WINDING<br/>WIDTH<br/>(mm)<br/>3*2.80<br/>Dimer<br/>(m</td><td>AVERAGE<br/>LENGTH OF<br/>TURN<br/>(mm)<br/>37</td><td>AREA<br/>PRODUCT<br/>Ae x Aw<br/>(mm<sup>4</sup>)<br/>610<br/>RE<br/>: EF1602<br/>FAY01091</td><td>EF-1602-2-3S-6P<br/>MARK<br/>Bobbin material: FR530<br/>Available for Fuan core: EF16/8/5</td></l≤45±0.30></l≤<br> | WINDING<br>AREA<br>(mm <sup>2</sup> )<br>32 | MINIMUM<br>WINDING<br>WIDTH<br>(mm)<br>3*2.80<br>Dimer<br>(m  | AVERAGE<br>LENGTH OF<br>TURN<br>(mm)<br>37  | AREA<br>PRODUCT<br>Ae x Aw<br>(mm <sup>4</sup> )<br>610<br>RE<br>: EF1602<br>FAY01091 | EF-1602-2-3S-6P<br>MARK<br>Bobbin material: FR530<br>Available for Fuan core: EF16/8/5 |  |
| NUMBER OF<br>SECTIONS<br>1<br>Tolerances unless of<br>D <l≤4±0.10 4<ls<br="">16<l≤4±0.30 45<br="">Pin Dim:±0.05 Thio</l≤4±0.30></l≤4±0.10>   | WINDING<br>AREA<br>(mm <sup>2</sup> )<br>32 | MINIMUM<br>WINDING<br>WIDTH<br>(mm)<br>3*2.80<br>Dimer<br>(m<br>ch:±0.20<br>Fuan Elect                                  | AVERAGE<br>LENGTH OF<br>TURN<br>(mm)<br>37<br>37<br>Mould No.<br>Code No.:<br>Code No.: | AREA<br>PRODUCT<br>Ae x Aw<br>(mm <sup>4</sup> )<br>610<br>RE                         | EF-1602-2-3S-6P<br>MARK<br>Bobbin material: FR530                                      |  |

COIL FORMER General data 6-pins EF16/8/5 coil former