COIL FORMER General data 10		6 coil former			
PARAMETER		SPECIFICATION			
Coil former material		phenolformaldehyde (PF), glass-reinforced, flame retardant in accordance with "UL 94V-0"; UL file number E59481			
Pin material		copper-tin alloy (CuSn), tin (Sn) plated			
Maximum operating temperature		180°C, "IEC 60085", class H			
Resistance to so	Idering heat	"IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s			
Soldeerability		"IEC 60068-2-20", Part 2, Test Ta, method 1			
		•		8) —+
				Ø0.60	4.000
Winding data a	- 10.00		13/6/6 coil form	her	
		-			
NUMBER OF SECTIONS	WINDING AREA (mm ²)	MINIMUM WINDING WIDTH (mm)	AVERAGE LENGTH OF TURN (mm)	AREA PRODUCT Ae x Aw (mm ⁴)	TYPE NUMBER
1	21	7.60	34	420	EI-1306-1S-10P
Tolerances unless otherwise specified: 0 <l<4±0.10< th=""> Dimensions: (mm) REMARK 16<l<45±0.30< td=""> 45≤L±0.40 Mould No.: Bobbin material: T375HF</l<45±0.30<></l<4±0.10<>					
Pin Dim:±0.05 Thic	kness:±0.20 Pin Pito	:±0.20 Code No.		FAY01144	Available for Fuan core: EE13/6/6
		Fuan Electronics TEL :0086-514-87693589 EML :sales@fuantronics.net		Make: P.Xiao	Material Number: A43133401305
	AIRUI			Checked: Beson. zhan Approved: Anson. zhan	Document/Rev: 00
			WEB:www.fuantronics.net		Date of Recognition: Nov./23/2019

COIL FORMER