

PYG40W-320W



Features

- Two-stage, Flicker-free
- PC programmable
- 0-10V/PWM Dim, 1-100% deep dimming
- Ambient temperature: -45-50 °C
- Dim to on
- Standby power <0.5W
- TA: -40 °C ~ +55 °C
- 6KV/10KV
- IP66//67

Power Supply For Outdoor Lighting

Models	Input Voltage (V)	Max Output Power(W)	Output Voltage (V)	Output Current (mA)	Efficiency %	Size(mm)
PYG40W-54-C1110-RP-P	100-277	40	27-54	100-1110	86	112*66*36.5
PYG40W-72-C0800-RP-P	100-277	40	36-72	100-800	87	112*66*36.5
PYG60W-54-C1670-RP-P	100-277	60	27-54	350-1670	88	112*66*36.5
PYG60W-86-C1100-RP-P	100-277	60	43-86	350-1100	88	112*66*36.5
PYG75W-56-C2100-RP-P	100-277	75	28-56	350-2100	88	145*66*36.5
PYG75W-107-C1050-RP-P	100-277	75	53-107	350-1050	88	145*66*36.5
PYG100W-56-C2670-RP-P	100-277	100	28-56	350-2670	92	145*66*36.5
PYG100W-107-C1400-RP-P	100-277	100	53-107	350-1400	92	145*66*36.5
PYG100W-192-C0690-RP-P	100-277	100	96-192	300-690	92	145*66*36.5
PYG150W-56-C4200-RP-P	100-277	150	28-56	700-4200	93	165*66*36.5
PYG150W-107-C2100-RP-P	100-277	150	53-107	500-2100	93	165*66*36.5
PYG150W-214-C1000-RP-P	100-277	150	107-214	350-1000	93	165*66*36.5
PYG200W-56-C5600-RP-P	100-277	200	28-56	700-5600	94	195*66*36.5
PYG200W-150-C2100-RP-P	100-277	200	75-150	500-2100	94	195*66*36.5
PYG200W-286-C1100-RP-P	100-277	200	143-286	350-1100	94	195*66*36.5
PYG240W-56-C6700-RP-P	100-277	240	28-56	700-6700	94	195*66*36.5
PYG240W-180-C2100-RP-P	100-277	240	90-180	500-2100	94	195*66*36.5
PYG240W-342-C1100-RP-P	100-277	240	171-342	350-1100	94	195*66*36.5
PYG320W-60-C7600-RP-P	100-277	320	30-60	1500-7600	94.5	243*76*42
PYG320W-240-C2100-RP-P	100-277	320	120-240	500-2100	94.5	243*76*42
PYG320W-457-C1000-RP-P	100-277	320	229-457	350-1100	94.5	241*76*41.5

FUAN ELECTRONICS

ADD: No. 58, Fuan East Road, Renhe Town, Tianchang City, Anhui Pro., China

TEL: +86(514)8769-3589 | EML: sales@fuantronics.net | WEB: www.fuantronics.net



Outdoor PC Programmable LED Driver



FUAN ELECTRONICS

📍 ADD: No. 58, Fuan East Road, Renhe Town, Tianchang City, Anhui Pro., China

☎ TEL: +86(514)8769-3589 | ✉ EML: sales@fuantronics.net | 🌐 WEB: www.fuantronics.net

